

RTS Torque Wrench

RTS offer an extensive range of Manual Torque Wrenches covering a range up to 4500Nm. We are able to offer a wrench for every application to suit your preference.

Torque Wrench

Features

- Dual Scale, Nm / Ft.Lbs.
- Accurately calibrated and certified to +/- of 4% tolerance with our high quality NATA certified calibration equipment.



Part No.	Model	Square drive	Torque Wrench		Weight g	Dim.(mm)	
			lb.ft	Nm		H	L
RTSW-25	Professional TW 2-25Nm	1/4"	1.5-1.8	2-25	410	36	296
RTSW-50	Professional TW 5-50Nm	3/8"	3.5-37	5-50	470	36	333
RTSW-100	Professional TW 10-100Nm	1/2"	8-75	10-100	820	36	400
RTSW-200	Professional TW 20-200Nm	1/2"	10-150	20-200	1300	36	500
RTSW-300	Professional TW 60-300Nm	1/2"	45-220	60-300	1470	36	635
RTSW-600	Professional TW 100-600Nm	3/4"	75-440	100-600	4650	TBA	1040
RTSW-1000	Professional TW 200-1000Nm	3/4"	150-740	200-1000	5450	TBA	1240

Part No.	Model	Spigot (mm)	Torque Wrench		Weight g	Length in mm
			lb.ft	Nm		
RTSTH-50	Professional TH 5-50Nm	16	3.5-37	5-50	530	330
RTSTH-100	Professional TH 10-100Nm	16	8-75	10-100	1050	440
RTSTH-200	Professional TH 20-200Nm	16	10-150	20-200	1230	510

Aluminium Torque Wrench

Features

- Light weight yet robust
- Accurately calibrated and certified +/- of 4% tolerance with our high quality NATA certified calibration equipment.
- Supplied in a weather-proof case and with a certificate of calibration.



PART NO.	Square drive	Torque Wrench		Weight g	Dim.(mm)
		lb.ft	Nm		
RTSTW-120A	1/2"	15-90	20-120	1300	475
RTSTW-200A	1/2"	30-150	40-200	1500	565
RTSTW-300A	1/2"	35-220	50-300	1500	625
RTSTW-550A	3/4"	80-400	110-550	3000	825
RTSTW-760A	3/4"	100-560	140-760	3000	825
RTSTW-1000A	3/4"	140-740	200-1000	3800	1415
RTSTW-1500A	1"	445-1110	600-1500	10900	1615
RTSTW-2000A	1"	555-1475	750-2000	11700	2370