RAD **SMART SOCKETS**™

Instant torque read-out of your live application!
Strain gauge technology measures torque applied to bolt. Patented Product.

The RAD Smart Sockets™ use RAD Torque's transducer technology combined with a custom socket to measure the actual torque applied to the bolt during a torque cycle. By innovative design, the Smart Sockets™ is no larger than a standard socket. Its compact size and innovative technology makes the Smart Sockets™ a perfect audit tool for inspecting bolted joints and it can function as a master calibration for various torque tools.

- Measures and displays peak torque
- Full data collection - export to email by PDF, XLS, CSV
- View in real time via Bluetooth onto your smartphone or tablet
- Transducer accuracy of +/-1%

ANDROID APP ON Google play

LABORATORY ACCREDITATION BUREAU a division of A2LA
ACCREDITED ISO/IEC 17025
Certificate # L2325 Calibration

PART NUMBER	SMART SOCKET MODEL	TORQUE (ft. lbs.) LOW	TORQUE (ft. lbs.) HIGH	DRIVE SIZE	WEIGHT (lbs.)	DIMENSION HEIGHT	DIMENSION DIAMETER
20879	33mm SMART SOCKET™	150	1500	3/4"	2.65	3.94"	2.83"
21363	36mm SMART SOCKET™	150	1500	1"	2.65	3.94"	2.83"
22158	41mm SMART SOCKET™	150	1500	1"	2.65	3.42"	2.83"
20880	46mm SMART SOCKET™	150	1500	1"	2.65	3.42"	2.83"
20881	50mm SMART SOCKET™	300	3400	1"	3.20	3.50"	3.40"
20882	55mm SMART SOCKET™	300	3400	1"	3.20	3.50"	3.40"
20883	60mm SMART SOCKET™	300	3400	1"	3.20	3.50"	3.40"
23690	65mm SMART SOCKET™	800	8000	1.5"	8.7	4.75"	4.53"
20884	70mm SMART SOCKET™	800	8000	1.5"	8.7	4.75"	4.53"
20885	80mm SMART SOCKET™	800	8000	1.5"	8.7	4.75"	4.53"
25657	90mm SMART SOCKET™	800	12000	1.5"	12.8	5.15"	4.53"
25658	100mm SMART SOCKET™	800	12000	1.5"	15.9	5.75"	4.73"

Accuracy of +/-1%